

WiFi Smart Alarm System Starter Kit TX-84

WiFi Basis Station with PIR Detection Sensor, Door/Window Contact & Remote Control



32

Verbindung von max. 32 Sensoren / Connection of max. 32 Detectors

200m

Übertragungsbereich von Sensoren zur Basisstation / Transmission Range from Detectors to Basis Station

868 MHz

Zwei-Wege Kommunikation zwischen Basisstation & Sensoren / Two Way Communication between Basis Station & Detectors

Push-Nachricht via APP bei Ereignissen & Bewegungserkennung / Push Message via APP at Events & Motion Detection

SOS

SOS-Knopf für Notruf-Push-Nachricht / SOS Button for Emergency Push Message

RF

Ein-/Ausschalten über Fernbedienung oder APP / On/Off via Remote Control or APP

TECHNAXX My Secure Pro

Installation & Konfiguration über My Secure Pro APP / Installation & Settings via My Secure Pro APP

25m

WiFi-Übertragungsbereich vom Router zur Basisstation / WiFi transmission from Router to Basis Station

12m PIR

PIR-Bewegungserkennung / PIR Motion Detection

2.4 GHz

Funkübertragung mit 2.4GHz / Wireless Transmission with 2.4GHz

- Modularly expandable, connect max. 32 detectors
- Connection with up to 6 remote controls
- Push message at alarm release & emergency call
- Two-way communication between detector & basis station
- Transmission distance from detectors to basis station ~200m open areas
- Adjustable alarm tone volume (mute, silent, loud)
- Easy installation & configuration via Smartphone with My Secure Pro APP (iOS & Android)
- Activate & deactivate of the alarm system via remote control or APP
- 5V/2A power supply via USB power adapter

Technical specifications basis station TX-84:

- Embedded: Micro Controller & Linux OS
- 128-Bit AES encryption algorithm
- Wireless connections: up to 32 detectors (868MHz); up to 6 remote controls/transmission distance ~10m (open areas)
- Audio output: built-in loudspeaker (alarm tone only)
- WiFi protocol: IEEE 802.11b/g/n, distance ~25m
- Power supply (Micro USB): DC 5V/2A, max. 10W
- Working temperature: -10°C ~ +50°C
- Installation: wall mounting (indoor only)
- Weight / Dimensions: 96g / (L) 9.4x (W) 11.4 x (H) 1.8cm

Package Contents TX-84:

- WiFi basis station with 1x USB power adapter, 1x Micro USB cable, 3x screws, 3x dowels, 1x adhesive tape
- PIR detection sensor with 1x bracket (on the device), 4x screws, 4x dowels, 1x CR123A battery
- Door and window contact with 4x screws, 4x dowels, 1x CR123A battery, 2x adhesive tape
- Remote control with 1x CR2032 battery 3V (installed in device)
- CD
- User Manual

Article-No. 4689



WiFi Smart Alarm System Starter Kit TX-84

WiFi Basis Station with PIR Detection Sensor, Door/Window Contact & Remote Control



Features & technical specifications PIR detection sensor TX-85:

- Alarm release at motion detection with ~12m detection range
- Built-in vandalism alarm (case & wall)
- Two-way communication between PIR & basis station
- Transmission frequency/distance: 868MHz/~200m open areas
- Detection method: passiv infrared (not visible 6500 LUX illumination)
- Two levels of sensitivity adjustable
- Viewing angle 90° horizontal & 70° vertical
- Push message at low battery level
- Battery lifespan ~2.5–3 years
- Wall/corner installation indoor only (H: ~2,1–2,5m)
- Weight / Dimensions: 77g (without battery) / (L) 10.5 x (W) 6.2 x (H) 4.2cm
- *Also available as single device.*
EAN code 4260358122519, Article No. 4690



Features & technical specifications door & window contact TX-86:

- Sensor alarm triggering at ~2.5cm distance
- Built-in vandalism alarm (case & wall)
- Two-way communication between contact & basis station
- Transmission frequency/distance: 868MHz/~200m open areas
- Alarm prompt: Red LED
- Push message at low battery level
- Battery lifespan ~2.5–3 years
- Fix installation indoor only (screws or adhesive tape)
- Weight / Dimensions Sensor: 33g (without battery) / (L) 8.3 x (W) 3.8 x (H) 2.0cm
- Weight / Dimensions Magnet: 34g / (L) 8.3 x (W) 2.5 x (H) 2.0cm
- *Also available as single device.*
EAN code 4260358122526, Article No. 4691



Features & technical specifications remote control TX-87:

- SOS button for emergency calls with Push message
- 4 adjustments possible: activate, stay at home, disarm, SOS
- Display in the APP at low battery level
- Transmission frequency/distance: 868MHz/~10m open areas
- Weight / Dimensions: 20g (with battery) / (L) 6.2 x (W) 3.0 x (H) 1.4cm
- *Also available as single device.*
EAN code 4260358122533, Article No. 4692